

ABEL Closed Cup Flash Point Tester Model:Flash-170m



Acute Instruments Pvt Ltd
 31,33 & 35Ground Floor Sai Chambers,
 Plot 44, Sector 11,CBD Belapur, Navi Mumbai,400614 Maharashtra, India
 sales@acuteinstruments.com
 Tel 1 : +91 22 49629780 Tel 2: +91 22 49709780
 www.acuteinstruments.net



Methods	IP 170, ISO 13736 & IS1448 (P:20)
Cooling	In-out ports for external water/coolant circulator
Heating	Band Heater 300 watts @ 230 VAC
Heat Rate	Heat rate control with precise ten turn potentiometer
Stirring	Speed Control by Precise Potentiometer from 0 to 60 rpm
Ignition	Gas Igniter - Precise control for gas igniter
Test	Manual dipping, heater and stirrer can be switched off by using toggle switch.
LidAssembly	Permanently fixed sample cup cover with Stirrer, sample temperature sensor and Igniter for easy operation
SampleTemperature	SS PT 100 , Class A, with digital indication / Thermometer interchangeable
Bath Temperature	SS PT 100 , Class A, with digital indication / Thermometer interchangeable
Stirrer RPM	Digital Indication of RPM
Dimensions	W:220mm X D:300mm X H:325mm
Power Supply	230Volts : 50Hz : 600 Watts